

Low-thrust trajectory design and operations of PROCYON, the first deep-space micro-spacecraft.

Campagnola, S. (1), Ozaki, N. (2), Sugimoto, Y. (1), Yam, C. (1), Chen, H. (3), Kawabata, Y. (4), Ogura, S. (4), Sarli, B. (4), Kawakatsu, Y. (1), Funase, R. (2), Nakasuka, S. (2)

*1 Japan Aerospace Exploration Agency/ Institute of Space and Astronautical Science (JAXA/ISAS), Kanagawa, Japan *2 The University of Tokyo, Tokyo, Japan *3 Kyushu University, Fukuoka, Japan *4 The Graduate University for Advanced Studies, Kanagawa, Japan

PROCYON is a micro-spacecraft developed by The University of Tokyo and JAXA [1], which was launched on Dec. 3 as secondary payload of H-IIA (primary payload was Hayabusa2 [2]). PROCYON is the first deep-space micro-spacecraft; it was developed mainly by students, with a very short development time of about one year, and at low-cost. Depending on the launch date, PROCYON nominal trajectory involves one or two Earth flyby, and a low-altitude flyby of a near-Earth asteroid [3].

PROCYON has several mission objectives, including: demonstration of a micro-spacecraft bus for deep-space exploration; in-flight validation of telecommunication and propulsion system components; precise VLBI navigation using *chirp*-DDOR and combined Hayabusa2 and PROCYON one-way measurements; very-low-thrust flight path control; imaging of the geocorona; and asteroid close flyby observation and optical navigation.

This paper discusses PROCYON's low-thrust trajectory design and flight implementation, from before launch to the current status. We formulate the optimization problem in a high fidelity model, with constraints coming from the spacecraft design and from ground operation considerations. The optimization is performed with jTOP, a novel in-house software, which is first presented in this paper.

Using pre-launch spacecraft parameters, the launch window analysis is examined first in the linked-conics model (aka zero-radius sphere-of-influence patched-conics), and then in the high-fidelity model used also for spacecraft navigation. Surprisingly, while the results in the simplified model reflect those of the preliminary design [4], the results in the high-fidelity model are significantly different. In some cases, new low-dv, low time-of-flight solutions are found in the high-fidelity model, which were deemed unfeasible in the simplified model. One important example is the post-launch baseline trajectory, which is also first presented here.

As the start of continuous low-thrust operations was delayed, new baselines were computed and implemented. We discuss the effect of the delayed operations and present backup scenarios to target the Earth sphere of influence or a secondary target asteroid. An analysis is performed using first and second order expansions of the nominal trajectory (provided by jTOP) and low-thrust targeting on the B-Plane.

[1] Funase et al., *50kg-class Deep Space Exploration Technology Demonstration Micro-spacecraft PROCYON*, SSC 2014

[2] Tsuda et al, *System Design of Hayabusa2 - Asteroid Sample Return Mission to 1999JU3*, IAC 2012

[3] Ozaki et al. , *Preliminary Mission Design of PROCYON: A Micro Spacecraft to Asteroid*, ISSFD 2014

[4] Yam, *Launch Window and Sensitivity Analysis of an Asteroid Flyby Mission with Miniature Ion Propulsion System: PROCYON*, IAC 2014